



Blue	B8 (679)	310	-4	464.4	1.05	✓
Blue	B9 (697)	462	-5	392.6	1.21	✓
Blue	B10 (717)	374	-3	251.3	1.22	✓
Blue	B11 (738)	257	-9	343.2	1.07	✓
Blue	B12 (760)	259	-4	584.1	1.08	✓
Blue	B13 (783)	341	-2	615.3	1.41	✓
Blue	B14 (812)	428	-5	1,006.9	1.78	✓
YellowGreen	YG1 (577)	275	-3	597.0	1.25	✓
YellowGreen	YG2 (598)	234	-7	1,405.3	1.30	✓
YellowGreen	YG3 (615)	186	-1	2,199.4	1.35	✓
YellowGreen	YG4 (661)	392	-3	1,256.7	1.43	✓
YellowGreen	YG5 (679)	261	-1	886.2	1.37	✓
YellowGreen	YG6 (697)	355	2	584.5	1.60	✓
YellowGreen	YG7 (720)	293	-2	694.8	1.56	✓
YellowGreen	YG8 (750)	227	-2	822.3	1.42	✓
YellowGreen	YG9 (780)	413	-8	1,059.8	1.77	✓
YellowGreen	YG10 (812)	339	-1	920.6	2.07	✓
Red	R1 (661)	175	6	387.3	1.19	✓
Red	R2 (679)	167	5	530.8	1.05	✓
Red	R3 (697)	271	4	416.6	1.30	✓
Red	R4 (717)	221	5	363.0	1.11	✓
Red	R5 (738)	153	-1	652.6	1.16	✓
Red	R6 (760)	170	-1	943.2	1.32	✓
Red	R7 (783)	281	-3	1,282.6	1.64	✓
Red	R8 (812)	142	-6	923.2	2.09	✓

### Laser Settings

Laser	Laser Delay	Area Scaling Factor	Laser Power
YellowGreen	-40.35	1.17	51.01
Violet	-20.28	1.05	1.17
Blue	0.00	1.24	42.57
Red	19.98	1.12	65.56

FSC Area Scaling Factor: 1.24      Window Extension: 3

Flow Rate: 13.87      Temperature: 23 °C

### Specifications

FSC	% rCV:	< 6 (Recommended)
SSC	% rCV:	< 8 (Recommended)
YG3	% rCV:	< 6 (Recommended)
V3	% rCV:	< 6 (Recommended)
B3	% rCV:	< 6 (Recommended)
R3	% rCV:	< 6 (Recommended)
All Channels	% Gain Change:	< 100 (Recommended)