

Blue	B8 (679)	300	-14	474.0	2.04	✓
Blue	B9 (697)	448	-19	400.5	2.00	✓
Blue	B10 (717)	371	-6	258.9	1.66	✓
Blue	B11 (738)	264	-2	342.3	1.55	✓
Blue	B12 (760)	272	9	570.3	2.17	✓
Blue	B13 (783)	369	26	606.9	2.91	✓
Blue	B14 (812)	486	53	958.1	4.46	✓
YellowGreen	YG1 (577)	263	-15	601.8	1.56	✓
YellowGreen	YG2 (598)	227	-14	1,421.7	1.24	✓
YellowGreen	YG3 (615)	179	-8	2,196.3	1.24	✓
YellowGreen	YG4 (661)	374	-21	1,262.8	1.40	✓
YellowGreen	YG5 (679)	247	-15	891.6	1.49	✓
YellowGreen	YG6 (697)	335	-18	594.1	1.63	✓
YellowGreen	YG7 (720)	284	-11	697.9	1.20	✓
YellowGreen	YG8 (750)	232	3	808.3	1.92	✓
YellowGreen	YG9 (780)	437	16	1,035.7	3.10	✓
YellowGreen	YG10 (812)	382	42	877.5	4.94	✓
Red	R1 (661)	161	-8	396.4	2.32	✓
Red	R2 (679)	151	-11	544.6	2.60	✓
Red	R3 (697)	250	-17	433.2	2.58	✓
Red	R4 (717)	205	-11	360.1	1.81	✓
Red	R5 (738)	155	1	646.2	1.54	✓
Red	R6 (760)	178	7	918.9	2.64	✓
Red	R7 (783)	305	21	1,250.3	3.51	✓
Red	R8 (812)	163	15	892.9	5.04	✓

Laser Settings

Laser	Laser Delay	Area Scaling Factor	Laser Power
YellowGreen	-40.30	1.18	50.99
Violet	-20.25	1.06	1.10
Blue	0.00	1.24	42.57
Red	20.03	1.13	65.56

FSC Area Scaling Factor: 1.24 Window Extension: 3

Flow Rate: 13.13 Temperature: 22.6 °C

Specifications

FSC	% rCV:	< 6 (Recommended)
SSC	% rCV:	< 8 (Recommended)
YG3	% rCV:	< 6 (Recommended)
V3	% rCV:	< 6 (Recommended)
B3	% rCV:	< 6 (Recommended)
R3	% rCV:	< 6 (Recommended)
All Channels	% Gain Change:	< 100 (Recommended)