

Blue	B8 (679)	304	-10	453.5	1.51	✓
Blue	B9 (697)	456	-11	385.7	1.60	✓
Blue	B10 (717)	374	-3	249.9	1.27	✓
Blue	B11 (738)	265	-1	347.1	1.20	✓
Blue	B12 (760)	272	9	592.9	1.66	✓
Blue	B13 (783)	364	21	637.4	2.39	✓
Blue	B14 (812)	475	42	1,052.4	3.81	✓
YellowGreen	YG1 (577)	264	-14	589.5	1.66	✓
YellowGreen	YG2 (598)	223	-18	1,392.3	1.69	✓
YellowGreen	YG3 (615)	177	-10	2,147.1	1.63	✓
YellowGreen	YG4 (661)	374	-21	1,222.5	1.63	✓
YellowGreen	YG5 (679)	250	-12	865.1	1.68	✓
YellowGreen	YG6 (697)	338	-15	565.7	1.77	✓
YellowGreen	YG7 (720)	286	-9	690.8	1.32	✓
YellowGreen	YG8 (750)	231	2	832.4	1.57	✓
YellowGreen	YG9 (780)	432	11	1,093.7	2.47	✓
YellowGreen	YG10 (812)	373	33	982.3	3.85	✓
Red	R1 (661)	168	-1	379.9	1.67	✓
Red	R2 (679)	157	-5	517.6	1.77	✓
Red	R3 (697)	258	-9	407.6	1.91	✓
Red	R4 (717)	212	-4	348.4	1.21	✓
Red	R5 (738)	157	3	658.9	1.59	✓
Red	R6 (760)	178	7	964.5	2.42	✓
Red	R7 (783)	303	19	1,340.7	3.15	✓
Red	R8 (812)	159	11	988.4	4.47	✓

Laser Settings

Laser	Laser Delay	Area Scaling Factor
YellowGreen	-40.25	1.18
Violet	-20.25	1.06
Blue	0.00	1.24
Red	19.98	1.13

FSC Area Scaling Factor: 1.24 Window Extension: 3

Flow Rate: 13.04 Temperature: 23.2 °C

Specifications

FSC	% rCV:	< 6 (Recommended)
SSC	% rCV:	< 8 (Recommended)
YG3	% rCV:	< 6 (Recommended)
V3	% rCV:	< 6 (Recommended)
B3	% rCV:	< 6 (Recommended)
R3	% rCV:	< 6 (Recommended)
All Channels	% Gain Change:	< 100 (Recommended)