



Blue	B8 (679)	312	-2	466.6	1.19	✓
Blue	B9 (697)	474	7	396.1	1.32	✓
Blue	B10 (717)	379	2	253.7	1.35	✓
Blue	B11 (738)	261	-5	349.1	1.19	✓
Blue	B12 (760)	266	3	595.8	1.18	✓
Blue	B13 (783)	349	6	628.8	1.44	✓
Blue	B14 (812)	444	11	1,041.1	1.80	✓
YellowGreen	YG1 (577)	274	-4	593.1	1.23	✓
YellowGreen	YG2 (598)	229	-12	1,377.0	1.30	✓
YellowGreen	YG3 (615)	182	-5	2,139.6	1.34	✓
YellowGreen	YG4 (661)	387	-8	1,236.3	1.43	✓
YellowGreen	YG5 (679)	260	-2	875.7	1.39	✓
YellowGreen	YG6 (697)	355	2	584.6	1.61	✓
YellowGreen	YG7 (720)	293	-2	693.4	1.57	✓
YellowGreen	YG8 (750)	228	-1	823.4	1.39	✓
YellowGreen	YG9 (780)	414	-7	1,057.2	1.68	✓
YellowGreen	YG10 (812)	343	3	935.5	1.91	✓
Red	R1 (661)	176	7	387.1	1.16	✓
Red	R2 (679)	166	4	525.0	1.00	✓
Red	R3 (697)	274	7	416.1	1.26	✓
Red	R4 (717)	221	5	358.6	1.06	✓
Red	R5 (738)	156	2	657.4	1.09	✓
Red	R6 (760)	173	2	949.6	1.28	✓
Red	R7 (783)	287	3	1,299.6	1.59	✓
Red	R8 (812)	146	-2	945.3	2.00	✓

**Laser Settings**

Laser	Laser Delay	Area Scaling Factor
YellowGreen	-40.25	1.17
Violet	-20.20	1.06
Blue	0.00	1.24
Red	19.95	1.13

FSC Area Scaling Factor: 1.24      Window Extension: 3

Flow Rate: 13.23      Temperature: 22.8 °C

**Specifications**

FSC	% rCV:	< 6 (Recommended)
SSC	% rCV:	< 8 (Recommended)
YG3	% rCV:	< 6 (Recommended)
V3	% rCV:	< 6 (Recommended)
B3	% rCV:	< 6 (Recommended)
R3	% rCV:	< 6 (Recommended)
All Channels	% Gain Change:	< 100 (Recommended)