

Blue	B8 (679)	309	-5	469.0	1.54	✓
Blue	B9 (697)	466	-1	401.7	1.65	✓
Blue	B10 (717)	378	1	254.6	1.40	✓
Blue	B11 (738)	264	-2	345.5	1.25	✓
Blue	B12 (760)	270	7	583.9	1.66	✓
Blue	B13 (783)	362	19	622.6	2.25	✓
Blue	B14 (812)	470	37	1,001.4	3.67	✓
YellowGreen	YG1 (577)	273	-5	599.9	1.67	✓
YellowGreen	YG2 (598)	234	-7	1,408.0	1.51	✓
YellowGreen	YG3 (615)	184	-3	2,165.9	1.50	✓
YellowGreen	YG4 (661)	386	-9	1,257.9	1.69	✓
YellowGreen	YG5 (679)	256	-6	886.5	1.78	✓
YellowGreen	YG6 (697)	343	-10	576.3	1.94	✓
YellowGreen	YG7 (720)	291	-4	695.7	1.64	✓
YellowGreen	YG8 (750)	233	4	823.0	1.70	✓
YellowGreen	YG9 (780)	434	13	1,067.9	2.44	✓
YellowGreen	YG10 (812)	368	28	926.7	3.80	✓
Red	R1 (661)	165	-4	386.9	1.95	✓
Red	R2 (679)	157	-5	533.2	2.18	✓
Red	R3 (697)	258	-9	420.1	2.27	✓
Red	R4 (717)	212	-4	356.0	1.52	✓
Red	R5 (738)	156	2	653.7	1.48	✓
Red	R6 (760)	176	5	942.2	2.28	✓
Red	R7 (783)	299	15	1,299.9	2.91	✓
Red	R8 (812)	156	8	936.0	4.16	✓

Laser Settings

Laser	Laser Delay	Area Scaling Factor
YellowGreen	-40.20	1.18
Violet	-20.28	1.06
Blue	0.00	1.24
Red	19.90	1.13

FSC Area Scaling Factor: 1.24 Window Extension: 3

Flow Rate: 12.79 Temperature: 23 °C

Specifications

FSC	% rCV:	< 6 (Recommended)
SSC	% rCV:	< 8 (Recommended)
YG3	% rCV:	< 6 (Recommended)
V3	% rCV:	< 6 (Recommended)
B3	% rCV:	< 6 (Recommended)
R3	% rCV:	< 6 (Recommended)
All Channels	% Gain Change:	< 100 (Recommended)