

Blue	B8 (679)	319	5	467.1	0.97	✓
Blue	B9 (697)	486	19	397.5	1.15	✓
Blue	B10 (717)	386	9	255.0	1.14	✓
Blue	B11 (738)	265	-1	347.4	0.95	✓
Blue	B12 (760)	269	6	591.3	0.99	✓
Blue	B13 (783)	350	7	618.6	1.29	✓
Blue	B14 (812)	442	9	1,022.1	1.65	✓
YellowGreen	YG1 (577)	281	3	615.1	1.31	✓
YellowGreen	YG2 (598)	241	0	1,466.4	1.36	✓
YellowGreen	YG3 (615)	190	3	2,274.1	1.39	✓
YellowGreen	YG4 (661)	394	-1	1,256.9	1.47	✓
YellowGreen	YG5 (679)	264	2	899.6	1.41	✓
YellowGreen	YG6 (697)	356	3	594.9	1.61	✓
YellowGreen	YG7 (720)	297	2	704.5	1.60	✓
YellowGreen	YG8 (750)	230	1	839.3	1.42	✓
YellowGreen	YG9 (780)	417	-4	1,073.1	1.78	✓
YellowGreen	YG10 (812)	343	3	950.7	1.93	✓
Red	R1 (661)	175	6	376.5	1.41	✓
Red	R2 (679)	166	4	518.9	1.23	✓
Red	R3 (697)	274	7	412.0	1.49	✓
Red	R4 (717)	220	4	351.9	1.28	✓
Red	R5 (738)	156	2	654.0	1.34	✓
Red	R6 (760)	172	1	941.7	1.49	✓
Red	R7 (783)	286	2	1,294.3	1.79	✓
Red	R8 (812)	144	-4	933.3	2.20	✓

Laser Settings

Laser	Laser Delay	Area Scaling Factor
YellowGreen	-40.25	1.19
Violet	-20.33	1.07
Blue	0.00	1.24
Red	20.05	1.14

FSC Area Scaling Factor: 1.23 Window Extension: 3

Flow Rate: 13.44 Temperature: 24.9 °C

Specifications

FSC	% rCV:	< 6 (Recommended)
SSC	% rCV:	< 8 (Recommended)
YG3	% rCV:	< 6 (Recommended)
V3	% rCV:	< 6 (Recommended)
B3	% rCV:	< 6 (Recommended)
R3	% rCV:	< 6 (Recommended)
All Channels	% Gain Change:	< 100 (Recommended)