



Blue	B8 (679)	314	0	465.9	1.32	✓
Blue	B9 (697)	467	0	395.9	1.48	✓
Blue	B10 (717)	378	1	252.4	1.35	✓
Blue	B11 (738)	264	-2	345.3	1.18	✓
Blue	B12 (760)	269	6	587.7	1.31	✓
Blue	B13 (783)	353	10	614.6	1.69	✓
Blue	B14 (812)	458	25	1,000.6	2.49	✓
YellowGreen	YG1 (577)	279	1	596.7	1.31	✓
YellowGreen	YG2 (598)	245	4	1,417.7	1.17	✓
YellowGreen	YG3 (615)	192	5	2,195.5	1.20	✓
YellowGreen	YG4 (661)	391	-4	1,258.8	1.33	✓
YellowGreen	YG5 (679)	259	-3	885.4	1.30	✓
YellowGreen	YG6 (697)	348	-5	587.9	1.49	✓
YellowGreen	YG7 (720)	291	-4	696.4	1.14	✓
YellowGreen	YG8 (750)	229	0	822.0	1.18	✓
YellowGreen	YG9 (780)	422	1	1,052.8	1.72	✓
YellowGreen	YG10 (812)	355	15	928.4	2.45	✓
Red	R1 (661)	163	-6	383.9	1.50	✓
Red	R2 (679)	156	-6	527.2	1.50	✓
Red	R3 (697)	257	-10	420.7	1.72	✓
Red	R4 (717)	209	-7	354.9	1.30	✓
Red	R5 (738)	154	0	654.3	1.21	✓
Red	R6 (760)	173	2	941.9	1.61	✓
Red	R7 (783)	291	7	1,293.8	2.03	✓
Red	R8 (812)	151	3	934.2	2.82	✓

**Laser Settings**

Laser	Laser Delay	Area Scaling Factor
YellowGreen	-40.18	1.18
Violet	-20.45	1.06
Blue	0.00	1.24
Red	19.90	1.13

FSC Area Scaling Factor: 1.23      Window Extension: 3

Flow Rate: 10.99      Temperature: 23.9 °C

**Specifications**

FSC	% rCV:	< 6 (Recommended)
SSC	% rCV:	< 8 (Recommended)
YG3	% rCV:	< 6 (Recommended)
V3	% rCV:	< 6 (Recommended)
B3	% rCV:	< 6 (Recommended)
R3	% rCV:	< 6 (Recommended)
All Channels	% Gain Change:	< 100 (Recommended)